- ASCE's Standard Practice - Provides Procedures Overview

Betsy Woodhouse - Southwest Hydrology, University of Arizona

he American Society of Civil Engineers' (ASCE) Standard Practice for the Design and Operation of Precipitation Enhancement Projects, published in 2004, provides a useful overview of the topic and is intended to inform water managers and others who may be considering such a project. The roughly 50-page publication does not provide specific standards so much as a description of how cloud seeding ("precipitation enhancement") works from both scientific and practical perspectives.

The first two sections cover the historical and scientific background of cloud seeding. U.S. cloud seeding experiments date back to the 1940s, when dry ice was used as the seeding agent. The current state of the technology is addressed by four major organizations: ASCE, the Weather

Modification Association, American Meteorological Society, and World Meteorological Organization. Sections on cloud condensate, the growth of precipitation, and concepts of precipitation augmentation provide an informative tutorial on how precipitation forms and what factors influence its formation.


The bulk of the document focuses on project design, which should consider the geographic and temporal scope of the project, the method of seeding, selection of the seeding agent, data collection, siting of equipment, and legal and environmental concerns. The geographic extent of the project should include both target and control areas with very similar geography, climatology, and use. Seeding can be performed by both aerial and ground-based methods; the advantages and disadvantages of each

are addressed. Typical seeding agents include silver iodide, dry ice, organic substances, and hygroscopic agents such as finely ground salt particles.

Data collection is critical both for determining the timing of seeding and evaluating its effectiveness. Real-time data used for decision-making are available from several networks and use radar, satellites, instrumented observatory stations, rawinsondes (balloon-borne instruments), gauges, computer models, and specially designed instruments such as for measuring the supercooled liquid water content of clouds. Data from precipitation and stream gauges, remote sensing techniques, snow chemistry, and cloud models are used to evaluate the results of seeding activities.

see ASCE, page 34

Where Is Weather Modification Occurring?



CALIFORNIA

Precipitation augmentation www.dwr.water.ca.gov

COLORADO

Snowpack augmentation Various ski areas and water districts

IDAHO

Snowpack augmentation www.idahopower.com

KANSAS

Hail suppression www.kwo.org

NEVADA

Precipitation augmentation www.cloudseeding.dri.edu

NEW MEXICO

Precipitation augmentation (lighter blue = proposed project) www.just-clouds.com

NORTH DAKOTA

Hail suppression, rainfall augmentation swc.nd.gov/arb

OKLAHOMA

(program suspended)
Rainfall augmentation,
hail suppression
www.owrb.state.ok.us/hazard/
weather/wx_mod.php

TEXAS

Rainfall augmentation, hail suppression www.license.state.tx.us/ weather/weathermod.htm

UTAH

Snowpack augmentation www.water.utah.gov/cloudseeding/

WYOMING

Snowpack augmentation www.rap.ucar.edu/projects/wyoming

ASCE, continued from page 29

Operational aspects of cloud seeding are covered next. Key project personnel include meteorological staff, pilots specifically trained in cloud seeding, a director of operations, and support personnel. Decision-making requires close coordination and communication among these and others, such as local weather officials. Safety considerations include protection of personnel from hazards related to microwave radiation, seeding agents and dispensers, severe weather, and aircraft safety. In addition, operators must monitor for conditions that warrant suspension of operations, such as flooding, severe weather, avalanche conditions, or full reservoirs.

The final section briefly addresses evaluation of cloud seeding projects.

Although much knowledge is to be gained over the long term from project evaluation, a strong evaluation requires target areas to be randomly seeded or not, so as to develop two unbiased classes of storms for comparison. Unfortunately, most sponsors of cloud seeding projects want to maximize the immediate benefits and not forego any opportunity to enhance precipitation, thus randomized programs are rare. Alternative approaches are to compare the target area to a nonseeded control area, or to compare storm measurements from within and outside of the project area prior to and during the project to see if the relationship changed during the seeding program. Both direct and indirect measurements are used for evaluation. Direct measurements include precipitation and radar data, whereas

indirect measurements may include crop yield changes, stream runoff data, or chemical analyses using various tracers.

The document concludes with a glossary of terms and an extensive list of references. Although anyone seriously considering initiating a cloud seeding project would need to consult with trained scientists and practitioners as to the feasibility and cost of the method in the desired area, Standard Practice provides water managers and others with a strong base of information about how the process works, decisions that would need to be made, and other important considerations.

See American Society of Civil Engineers, 2004. Standard Practice for the Design and Operation of Precipitation Enhancement Projects, ASCE/EWRI 42-04.

Business Directory



326 South Wilmot Road Suite A-200 Tucson, AZ 85711 Tel.: 520.326.1898 info@HaleyAldrich.com HaleyAldrich.com

18 offices nationwide

Creative Solutions for Client Success

- · Environmental Remediation
- · Water Resource Investigations
- Environmental, Health, Safety Compliance
- Environmental & Regulatory Strategies



- Groundwater Development
- Fractured Reservoir Systems
- Groundwater Environmental
- · Geologic Mapping
- GIS and Remote Sensing

Clay Conway, Ph.D., R.G. (AZ) 715 W. 2nd South 52-4

Blanding, UT 84511

435-678-7821

conway@gaeaorama.com



To discuss your questions and applications, call 1-800-645-8469

Tel: 1-618-281-9416 Fax: 1-618-281-9473

www.tamintl.com/hydrological

Inflatable Packers

Applications include:

- Hydrological Testing
- Injection/Withdrawal
- Standard/Custom Sizes/Materials
- Water/Mining/Environmental
- · Grouting/Sampling/Geotechnical
- Hydrofracturing
- · Recirculation Wells
- Steam Injection
- Reline Casing



Environmental Investigations:

Ground-Water Supply Development & Evaluations Hydrogeological & Contaminant Transport Modeling Hydrogeological, Geological & Expert-Witness Investigations

E-Mail: mdc@mdcampbell.com Main Office: (713) 807-0021

Downhole Flow Control Valves for Aquifer Storage & Recovery

- · Reliable, cavitation free, sand resistant performance 2 to 12 inch and larger pump column pipe sizes
 - Inflatable Packers
- · Standard & Custom for all applications

100 to 7,000 psi; 1-1/2 to 60 inch holes

Baski, Inc.

Ph. 303 789-1200 or 800 552-2754 Fx. 303 789-0900

www.baski.com

1586 South Robb Way, Denver, Co 80232 USA

john i ward, rg groundwater consultant

- water supply
- peer review
- expert witness
- water rights
- litigation support
- due diligence

(520) 296-8627 phone: (520) 490-2435 email: ward_groundwater@cox.net web: www.wardgroundwater.com